



SIZE	ART. NO.	EAN NO.
7	134-7	7392626060326
8	134-8	7392626060333
9	134-9	7392626040625
10	134-10	7392626040632
11	134-11	7392626040649

## TEGERA® 134

Welding and heat-resistant glove, fully lined, full grain goatskin, cut resistance level C, KEVLAR® fiber, Nomex®, Cat. III, black, brown, extra long, reinforced seams, water and oil repellent, elasticated 180°, for allround work

### PROPERTIES

High level of protection, good fingertip sensitivity, durable, good fit

### SPECIFICATION

TYPE OF GLOVE Cut resistant gloves, Welding gloves

CATEGORY Cat. III

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 17.17

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

BACK MATERIAL Full grain goatskin

LINING Fully lined

LINING MATERIAL KEVLAR® fiber, Nomex®

DEXTERITY 4

CUFF STYLE Extended safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 395 mm

COLOUR Black, Brown

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

MIDDLE MATERIAL SPECIFICATION Meta-aramid

INNER MATERIAL SPECIFICATION Para-aramid

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 134

### FEATURES

Withstands contact heat up to 100°C, extra long, reinforced index finger, reinforced seams, water and oil repellent, withstands welding sparks and grinding splash

### PREVENTS RISK OF

Burn injuries, heat injuries, cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp

### PRIMARY ENVIRONMENTS OF USE

Cut risk environments, warm environments, moist environments, oily and greasy environments, harsh environments

### PRIMARY AREAS OF USE

Hot work, metalwork, sheet-metal work, welding

### PRIMARY INDUSTRIES OF USE


Metal fabrication, machinery and equipment, MRO, automotive

### TYPE OF WORK

Medium weight

 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 3X22C  EN 407:2004 41234X EN 12477:2001 + A1:2005

Type A EN 1149-2:1997 R:4,11x10<sup>11</sup>Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

2(3)

  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

# TEGERA® 134

## EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

## COMPLIANCE DESCRIPTION

EN 1149-2:1997 Electrostatic properties (vertical resistance)

EN 12477:2001 + A1:2005 Protective gloves for welders

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

## EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

Type A - Lower dexterity (with higher other performance)

**ejendals**  
PROTECTING HANDS AND FEET

### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com


order@ejendals.com

www.ejendals.com



CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 3X22C  EN 407:2004 41234X EN 12477:2001 + A1:2005

Type A EN 1149-2:1997 R:4,11x10<sup>11</sup>Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.