PRIMERO AIR CE

ΚΛͿΚ

FN

WHE00113



TECHNICAL DETAILS



MATERIAL EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE Universal-adjustable from 52 to 63 cm



WEIGHT 460 g



STANDARD

EN 50365 (Class 0) 😤 Protection against top, front, rear and side impacts in conformity with EN 12492 Clauses 4.2.1 shock energy absorption capacity Clause 4.2.2 penetration EN 397 additional tests: -30°C / LD / MM

TEMPERATURE OF USE

-30°C / +50°C







TECHNOLOGIES



POLYPROPILENE HD EXTERNAL SHELL

Lightweight external shell with exponential better performance. Excels in impact absorption, especially at lower temperatures (-30°C). Resists yellowing and degradation.



HD EPS INTERNAL SHELL

Inner shell composed of high-density foam for all-around impact energy absorption and improved comfort.



CLICK-IN SYSTEM

Enhanced padding attachment system that quickly secures into place and allows for easy replacement, and removal. Patented system improves padding durability.



2DRY LINER

A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



ERGO FIT SYSTEM

Helmet size adjusting system that allows for an easy and secure fit by turning the large diameter dial. The system moves up and down to adapt to a range of head shapes. The ergonomically shaped wings cradle the back of the neck for added comfort.



ADVANCED LITE CHINSTRAP

Chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.



LATERAL ADJUSTMENT DIVIDER

Side regulator point on chinstrap for adjustment and positioning for a more tailored fit.

RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.

EARMUFF ATTACHMENT SLOTS

Helmet designed with standard 30mm EURO slots for attaching KASK hearing protection earmuffs.

VENTILATION CHANNELS

555 Designed with 14 air intakes shaped to prevent debris entry and internal channels for enhanced breathability and wearer comfort. < 8 8 8



EARPLUG HOOKS

Lamp clip feature that holds corded earplugs.

FRONTAL ACCESSORY SLOT

Front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps. Includes cap cover for debris protection.

(in)

PRIMERO AIR CE

ΚΛ/Κ

FN

TECHNOLOGIES



NECK PROTECTOR SLOT

3 rear helmet slots for mounting KASK Neck Protection products.

EASY CLICK SYSTEM

Helmet designed with integrated slots for easy mounting of KASK eye and face protection accessories. Easy Click Visor Adapters required.

PERFORMANCES

Protection against top impacts		5 kg from 1 m 50 J	Chinstrap release	K	>15 kg <25 kg
Protection against side, front and rear impacts	K *	5 kg from 0,5 m 25 J	Lower temperature resistance test	K	T= -30°C
Protection against top impacts		5 kg from 2 m 100 J	Protection against side deformation	K	LD
Protection against the penetration of objects	K	3 kg from 1 m 30 J	Protection against molten metal splashes	K	MM

K EN 397 standard requirements **K**^{*}Additional compliance in conformity with the requirements of EN12492

K EN 397 additional requirements



ADDITIONAL INFORMATION

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

GUARANTEE

3 years starting from the date of purchase.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WVI00007

ZEN VISOR

WVI00022-500

ZEN FACE SHIELD



ZEN FULL FACE VISOR



WVI00009/10 ZEN MM/PM VISOR



REPLACEABLE LAMP CLIPS

elastic bands.

Helmet designed with 4 removable nylon lamp attachment clips. Compatible with KASK headlamps and other headlamps with







DISCOVER MORE







WLA00001/2/3

HEADLAMPS



WPA00007 WINTER PADDING







 \bigcirc



KASK S.p.A. / Via Firenze, 5 - 24060 Chiuduno (BG) - Italy T. +39 035 4427497 / F. +39 035 4427704 / info@kask.com

in \bigcirc