



Technical Details

EXTERNAL SHELL: P.P. Polypropylene
 INTERNAL SHELL: HD Expanded polystyrene
 HEADBAND: Soft PA Nylon
 SIZE: Universal-adjustable from 53 to 63 cm
 STANDARD: EN 397 – EN 50365 (Class 0)



400 g



-30°C / +50°C

WHE00024.201
WHITEWHE00024.202
YELLOWWHE00024.203
ORANGEWHE00024.204
REDWHE00024.205
GREENWHE00024.208
BLUEWHE00024.210
BLACKZenith XL
newWHE00050.201
WHITE
(XL fit)WHE00050.202
YELLOW
(XL fit)

Technology

ELECTRIC SHOCK
PROTECTION

PROTECTION AGAINST ELECTRIC SHOCK: Helmet provides protection against electrical hazards for use in the vicinity of low voltage systems with voltages up to 1500V DC or 1000V AC.



CLIP

LAMP CLIPS: Helmet is equipped with strong removable carrying clips, compatible with all headlamps with elastic bands on the market.

CHINSTRAP
EN 397

CHINSTRAP EN 397: Four point chinstrap fixed to the external shell without metal rivets with Quick release fastening and opening in conformity with EN 397. Provided with lateral divider for adjusting the length of the straps.



ECO

ECO LEATHER CHINSTRAP: Eco-leather, hypoallergenic, washable chinstrap which is extremely comfortable and helps avoid irritation of the skin.



RING TO HOOK

RING TO HOOK: Fitted with a special hook on the chinstrap which allows the helmet to be connected to the harness.



FRONT PAD

REMOVABLE FRONT PAD: Front-end padding easily removable and washable. Developed to guarantee maximum breathability and optimum moisture absorption. Designed to adhere to the front, optimizing comfort.



FAST3DRY

FAST 3DRY: High-tech 3D fabric that dries very quickly, helping the dispersion of moisture to the outside and leaving a pleasant feeling.



UP&DOWN 2.0

UP & DOWN 2.0: The innovative and exclusive UP & Down 2.0 technology ensures a precise and comfortable fit around the back of the head. The center wheel and the two side wings allow the quick adjustment of the helmet not only in width but also in height and tilt.



VISOR

VISOR ATTACHMENT: Provided with attachment for fitting Zenith visors.



EARMUFFS

EARMUFFS FITTING: Built with integrated slot for earmuffs. Compatible with KASK earmuffs.

Performances

PROTECTION AGAINST TOP IMPACTS	5 Kg from 2 m 100 J
PROTECTION AGAINST SIDE, FRONT AND REAR IMPACTS	5 Kg from 0,5 m 25 J
PROTECTION AGAINST THE PENETRATION OF OBJECTS	3 Kg from 1 m 30 J
PROTECTION AGAINST ELECTRIC SHOCK	
CHIN STRAP RELEASE > 15 kg <25 kg	
RETENTION SYSTEM EFFECTIVENESS	
LOWER TEMPERATURE RESISTANCE TEST	T= -30°C
PROTECTION AGAINST SIDE DEFORMATION- LD	
PROTECTION AGAINST MOLTEN METAL SPLASHES- MM	



Standard requirements

Additional test in conformity with the requirements of the EN 12492

Optional requirements

Additional Information



GUARANTEE

3 years starting from the purchasing date.

SHELF LIFE

10 years starting from the production date (production date is printed on a label contained on the inside of the helmet). Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

CLEANING

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

STORAGE

When not in use the helmet should be stored away from direct sunlight or source of heat.

ADHESIVE APPLICATION

Do not apply adhesives, solvents, stickers or paint that do not comply with the manufacturer's specifications. Any alteration or intervention not provided for may impair its protective function.

Accessories



WVI00007
ZEN VISOR

WVI0009/10
ZEN MESH VISOR

WVI00008
ZEN FULL FACE

WVI00016 / WVI00017
ARC FLASH VISOR

WAC00009
VISOR ADAPTOR

WAC00010
VISOR CARRIER

WVI00011
ZEN PEAK

WAC00011
4 PIECES OF LAMP CLIPS

WPA00006
REPLACEMENT INNER PADDING

WAC00013
NECK SHADE

WAC00025
NECK SHADE HI VIZ

WHP00004/5/6
EARMUFFS

WPA00007
WINTER PADDING

WAC00026
HELMET BAG